



T Onyx 120C ep79 HA84



T Onyx 140R ep79 MH-A84



T Onyx 2212CD epa83 HP96




T Onyx 2212C epa83 HP88



T Onyx 2412CD epa83 HP96

EPOXY (ep../epa..) - Ø 40x40 mm - HT75 - incl. regelschroef - vis de réglage - Stellschraube - adjusting screw

Onyx HPL / HA / HM / MEL / MHA



		120C	100	110	120	120D	140R	120V	2212C	2412E	189	210	120CD	100CD	159C	2212CD	2412CD	181C
L x B		circ. 120x120	Ø100	Ø110	Ø120	Ø120+40x120	Ø140	120x120	Danish oval 220x120	ellipse 240x120	180x90	200x100	circ. 120+40x120	circ. 100+40x100	Danish oval 150x90	Danish oval 220+80x120	Danish oval 240+80x120	Danish oval 180x100
H (hpl)	ht75 ht90	76,0 91,0	76,0 91,0	76,0 91,0	76,0 91,0	75,8 90,8	75,2	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8	75,8 90,8
BD (mm)	HPL/HA HM MEL/MHA	26 mm - -	26 mm 18 mm -	26 mm - -	26 mm - -	24 mm - -	- - 18 mm	24 mm - -	24 mm - -	24 mm - -	24 mm 18 mm -	24 mm 18 mm -	24 mm - -	24 mm - -	24 mm - -	24 mm - -	24 mm - -	24 mm - -
PH PB PL	HT75	73,6 - -	73,6 - -	73,6 - -	73,6 - -	73,4 - -	72,8 - -	73,4 - -	73,4 - 99,0	73,4 - 99,0	73,4 - 99,0	73,4 - 99,0	73,4 - 99,0	73,4 - 99,0	73,4 - 99,0	- - -	- - -	- - -
m³ (ht75)		0,19	0,15	0,17	0,19	0,19	0,24	0,19	0,31	0,32	0,21	0,25	0,19	0,15	0,18			0,23
kg (ht75)	HPL/HA HM MEL/MHA	31,8-36,3 - -	23,8-27,4 23,7-27,3 -	26,6-30,5 - -	29,4-33,9 - -	47,3-52,1 - -	- - 29,8-36,1	32,5-37,0 - -	53,9-62,6 - -	53,4-61,2 - -	39,3-44,9 39,2-44,8 -	45,3-51,3 45,2-51,2 -	50,0-54,2 - -	39,9-43,1 - -	28,7-33,2 - -	86,6-99,2 - -	90,5-103,1 - -	34,0-41,4 - -